DOUGLAS AIRCRAFT CO. ATTN: MYA ANDERSON . 3855 LAKEWOOD BLVD. INTERNAL MAIL 126-14 LONG BEACH, CA 90846



DOW CORNING CORPORATION MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) (1200 PRIME COAT - CLEAR

EMERGENCY TELEPHONE NO. (517) 496-5900

SECTION I - GENERAL INFORMATION

MANUFACTURERS NAME: DOW CORNING CORPORATION ADDRESS: SOUTH SAGINAW ROAD, MIDLAND MI 48686

PROPER SHIPPING NAME(49CFR 172.101): FLAMMABLE LIQUID NOS

PROPER SHIPPING NAME(49CFR 1/2.101): FLAMMABLE LIQUID.O.T. HAZARD NAME(49CFR 1/2.101): NAPHTHA
D.O.T. ID NO(49CFR 1/2.101): UN 1993
D.O.T. HAZARD CLASS(49CFR 1/2.101): FLAMMABLE LIQUID.
RCRA HAZARD CLASS(40CFR 261)(IF DISCARDED): IGNITATE.P.A. PRIORITY POLLUTANTS(40CFR 122.53): NONE
NFPA = NATIONAL FIRE PROTECTION ASSOCIATION - 704
HEALTH (NFPA): 2 FLAMMABILITY (NFPA): 3
RECAS NO: MIXTURE

IGNITABLE (D001)

REACTIVITY (NFPA): 0 DOW CORNING WARNING CODE: 58

CAS NO: MIXTURE GENERIC DESCRIPTION: ORGANSILICATE IN SOLVENT

SECTION II - HAZARDOUS INGREDIENT

VM&P NAPHTHA **ORGANOSILICATE** % 85 % 5

TLV (UNITS): 300PPM; PEL500PPM

TLV (UNITS): 5 PPM;25 PPM

ONLY THOSE INGREDIENTS LISTED IN THIS SECTION HAVE BEEN DETERMINED TO BE HAZARDOUS AS DEFINED IN 29 CFR 1910.1200. AN INGREDIENT MARKED WITH AN ASTERISK(*) IS ALSO LISTED IN 29 CFR 1910.1200(D) #4 AS KNOWN OR SUSPECTED CARCINOGEN.

COMMENT: TLV FOR ORGANOSILICATE BASED ON LIBERATED 2-METHOXYETHANOL.

DOW CORNING CORPORATION MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 1200 PRIME COAT - CLEAR

SECTION III - EFFECTS OF OVEREXPOSURE

EYES: MAY IRRITATE WITH SLIGHT PAIN, REDNESS, AND POSSIBLE MINOR CORNEAL INJURY.

SKIN: A SINGLE EXPOSURE FOR SEVERAL HOURS MAY CAUSE SLIGHT REDDENING. LONGER OR REPEATED CONTACTS MAY CAUSE MODERATE IRRITATION AND POSSIBLY A MILD BURN.

INHALATION: SHORT EXPOSURE MAY CAUSE SLIGHT ANESTHESIA AND POSSIBLY SOME INJURY, DEPENDING ON CONCENTRATION AND LENGTH OF EXPOSURE. MAY ALSO IRRITATE NOSE AND THROAT SLIGHTLY.

ORAL: AMOUNTS TRANSFERRED TO THE MOUTH BY FINGERS, ETC., DURING NORMAL OPERATIONS SHOULD NOT CAUSE INJURY.

COMMENT: 2-METHOXYETHANOL (METHYL CELLOSOLVE) MAY FORM UPON HYDROLYSIS.
ANIMAL REPRODUCTIVE STUDIES HAVE SHOWN 2-METHOXYETHANOL IS ABLE TO CAUSE
ANIMAL BIRTH DEFECTS.

THIS PRODUCT, AS WITH ANY CHEMICAL, MAY ENHANCE ALLERGIC CONDITIONS ON CERTAIN PEOPLE. WE DO NOT KNOW OF ANY MEDICAL CONDITIONS THAT MIGHT BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

SECTION IV - EMERGENCY AND FIRST AID PROCEDURES

EYES: FLUSH WITH WATER.

SKIN: WIPE OFF AND FLUSH WITH WATER.

INHALATION: REMOVE TO FRESH AIR. OBTAIN IMMEDIATE MEDICAL ATTENTION.

ORAL: OBTAIN IMMEDIATE MEDICAL ATTENTION.

COMMENT: NONE

SECTION V - FIRE AND EXPLOSION DATA

FLASH POINT (METHOD USED): CLOSED CUP 63°F/17°C

AUTOIGNITION: NOT DETERMINED

FLAMMABILITY LIMITS IN AIR : LOWER: N.D. UPPER: N.D.

EXTINGUISHING MEDIA: WATER WATER FOG X CO2 X DRY CHEMICAL X FOAM X OTHER

SPECIAL FIRE FIGHTING PROCEDURES: SELF_CONTAINED BREATHING APPRARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN TO DOW CORNING

COMMENTS: N.D. - NOT DETERMINED

SECTION VI - PHYSICAL DATA

BOILING POINT(a 760 MM HG): 210°F/99°C

SPECIFIC GRAVITY (AT 77 DEG F/25 DEG C): 0.773

MELTING POINT: NOT APPLICABLE

VAPOR PRESSURE (AT 77 DEG F/25 DEG C): 25 MM

VAPOR DENSITY (AIR = 1 AT 77 DEG F/25 DEG C): GREATER THAN 1

PERCENT VOLATILE BY VOLUME (%): ABOVE 70%

EVAPORATION RATE (ETHER = 1): LESS THAN 1

SOLUBILITY IN WATER(%): LESS THAN 0.1%

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPA

ODOR, APPEARANCE, COLOR: SOLVENT ODOR, LIQUID, CLEAR

NOTE: THE ABOVE INFORMATION IS NOT INTENDED FOR USE IN PREPARING PRODUCT SPECIFICATIONS. CONTACT DOW CORNING BEFORE WRITING SPECIFICATIONS

DOW CORNING CORPORATION MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 1200 PRIME COAT - CLEAR

SECTION VII - REACTIVITY DATA

STABILITY: STABLE

INCOMPATABILITY (MATERIAL TO AVOID): OXIDIZING MATERIAL CAN CAUSE A REACTION.

CONDITIONS TO AVOID: NOT APPLICABLE

HAZARDOUS DECOMPOSITION PRODUCTS: SILICON DIOXIDE, CARBON DIOXIDE, AND TRACES OF INCOMPLETELY BURNED CARBON PRODUCTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NOT APPLICABLE.

COMMENTS: NONE

SECTION VIII - SPILL, LEAK AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: USE ABSORBENT MATERIAL TO COLLECT AND CONTAIN FOR SALVAGE OR DISPOSAL. REMOVE ALL SOURCES OF IGNITION AND WEAR PROPER PROTECTION EQUIPMENT.

PROTECTIVE EQUIPMENT:

EYES: USE CHEMICAL WORKER GOGGLES.

SKIN: REMOVE CONTAMINATED CLOTHING AND SHOES AT THE END OF THE WORK PERIOD AND CLEAN THOROUGHLY BEFORE REUSE.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES.

WASTE DISPOSAL METHOD: DOW CORNING SUGGESTS THAT ALL LOCAL, STATE AND FEDERAL REGULATIONS CONCERNING HEALTH AND POLLUTION BE REVIEWED TO DETERMINE APPROVED DISPOSAL PROCEDURES. CONTACT DOW CORNING IF THERE ARE ANY DISPOSAL QUESTIONS.

D.O.T. (49CFR 171.8)/E.P.A. (40CFR 117) SPILL REPORTING INFORMATION HAZARDOUS SUBSTANCE: NONE REPORTABLE QUANTITY: NOT APPLICABLE CONCENTRATION OF HAZARDOUS SUBSTANCE: NOT APPLICABLE REPORTABLE QUANTITY OF PRODUCT: NOT APPLICABLE

COMMENTS: NONE

SECTION IX - ROUTINE HANDLING PRECAUTIONS

PROTECTIVE EQUIPMENT:

EYES: USE PROPER PROTECTION -- SAFETY GLASSES, AS A MINIMUM.

SKIN *: WASHING AT MEALTIME AND END OF SHIFT IS ADEQUATE.

INHALATION: USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST VENTILATION IS ADEQUATE, OR AIR SAMPLING DATA SHOW EXPOSURES ARE WITHIN TLV AND PEL GUIDELINES.

VENTILATION:

LOCAL EXHAUST: RECOMMENDED

MECHANICAL (GENERAL): RECOMMENDED

SUITABLE RESPIRATOR: ORGANIC VAPOR TYPE.

THESE PRECAUTIONS ARE FOR ROOM TEMPERATURE HANDLING, USE AT ELEVATED TEMPERATURE MAY REQUIRE ADDED PRECAUTIONS.

* GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY CHEMICAL BE REMOVED FROM THE SKIN AS SOON AS PRACTICAL, ESPECIALLY BEFORE EATING OR SMOKING. COMMENTS: NONE

DOW CORNING CORPORATION MATERIAL SAFETY DATA SHEET

MATL NAME: DOW CORNING(R) 1200 PRIME COAT - CLEAR

SECTION X - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: PRODUCT IS FLAMMABLE. USE REASONABLE CARE AND CAUTION.

OTHER PRECAUTIONS: NONE KNOWN TO DOW CORNING. COMMENTS: NONE

THESE DATA ARE OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE WHETHER THEY ARE APPROPRIATE.

PREPARED BY: JACK L. SHENEBERGER LAST REVISION DATE: SEPTEMBER 20, 1985 PREVIOUS REVISION DATE: MARCH 19, 1984 DATE: OCTOBER 03, 1986

(R) INDICATES REGISTERED OR TRADEMARK OF THE DOW CORNING CORPORATION.